

according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Foam

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Lorencic GmbH Nfg. & Co KG		
Street:	Puchstraße 208		
Place:	A-8055 Graz		
Telephone:	+43 (0) 316 / 47 25 64 32	Telefax: +43 (0) 316 / 47 25 64 78	
Responsible Department:	Dr. Gans-Eichler	e-mail: info@tge-consult.de	
	Chemieberatung GmbH	Tel.: +49(0)2534 6441185	
	Otto-Hahn-Str. 36	www.tge-consult.de	
	D-48161 Münster		
1.4. Emergency telephone	Poison Control Centre Vienna: +43 (0) 1 406 43 43		

1.4. Emergency telephone

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories: Aerosol: Aerosol 1 Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Resp. Sens. 1 Respiratory or skin sensitisation: Skin Sens. 1 Carcinogenicity: Carc. 2 Reproductive toxicity: Lact. Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Acute 1 Hazardous to the aquatic environment: Aquatic Chronic 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 2 of 16

Hazard components for labelling

alkanes, C14-17, chloro; chlorinated paraffins, C14-17 4,4'-methylenediphenyl diisocyanate, isomers and homologues

Danger

Signal word: **Pictograms:**

Hazard statements

	-	
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H362	May cause harm to breast-fed children.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H410	Very toxic to aquatic life with long lasting effects.	
ecautionary sta	tements	
P101	If medical advice is needed, have product container or label at hand.	

Precautionary s	atements
P101	If medical advice is needed, have product container or label a

- P102 Keep out of reach of children.
- P210 Keep away from heat. No Smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container to in accordance with official regulations.

Special labelling of certain mixtures

	J · · · · ·	
EUH204		Contains isocyanates. May produce an allergic reaction.
		Persons already sensitised to diisocyanates may develop allergic reactions when using
		this product. Persons suffering from asthma, eczema or skin problems should avoid
		contact, including dermal contact, with this product. This product should not be used under
		conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.
		type A1 according to standard EN 14387) is used.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The mixture contains the following substances fulfilling the PBT-/vPvB criteria according to REACH Annex XIII: Decamethylcyclopentasiloxane, Dodecamethylcyclohexasiloxane, Octamethylcyclotetrasiloxane

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No Index No REACH No			
	GHS Classification			
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17			40 - < 60 %
	287-477-0	602-095-00-X	01-2119519269-33	



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 3 of 16

	Lact., Aquatic Acute 1, Aquatic Chronic 1; H362 H400 H410 EUH066			
9016-87-9	4,4'-methylenediphenyl diis	ocyanate, isomers and homologu	ies	20 - < 40 %
		615-005-01-6		
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
115-10-6	dimethyl ether			5 - < 10 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas; H220 H280			
25322-69-4	Propane-1,2-diol, propoxylated		5 - < 10 %	
	500-039-8			
	Acute Tox. 4; H302	•	*	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
85535-85-9	287-477-0	alkanes, C14-17, chloro; chlorinated paraffins, C14-17	40 - < 60 %
	inhalation: LC50 = > 48,17 mg/l (vapours); dermal: LD50 = > 2800 mg/kg; oral: LD50 = > 4000 mg/kg M acute; H400: M=1 M chron.; H410: M=1		
9016-87-9		4,4'-methylenediphenyl diisocyanate, isomers and homologues	20 - < 40 %
	inhalation: LC50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
25322-69-4	500-039-8	Propane-1,2-diol, propoxylated	5 - < 10 %
	dermal: LD50	= >2000 mg/kg; oral: LD50 = 1000-2000 mg/kg	

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. Apply cortisone spray at early stage.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration! Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 4 of 16

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). Hydrogen chloride (HCI)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains. In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Ventilate affected area. Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. Eliminate leaks immediately. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 5 of 16

cellars, flues and ditches.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Remove contaminated clothing immediatley and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking. Provide adequate ventilation.

Hints on joint storage

Do not store together with: Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. Self-reactive substances and mixtures. Organic peroxides. Radioactive substances.

Infectious substances.

Further information on storage conditions

Recommended storage temperature: 10-30°C. Do not store at temperatures over: 50°C Note: Storage requirements for flammable aerosols.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17			
Worker DNEL, long-term inhalation systemic 6,7 mg/m³		6,7 mg/m³		
Worker DNEL, long-term		dermal	systemic	47,9 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2 mg/m³
Consumer DNEL, long-term		dermal	systemic	28,75 mg/kg bw/day



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021	Product code: ZKR13GX		Page 6 of 16
Consumer DNEL, long-term	oral	systemic	0,58 mg/kg bw/day
9016-87-9 4,4´-methylenediphenyl diisocyanate, isom	ers and homologues		
Consumer DNEL, acute	inhalation	local	0,05 mg/m³
Consumer DNEL, long-term	inhalation	local	0,0025 mg/m³
Worker DNEL, acute	inhalation	local	0,1 mg/m ³
Worker DNEL, long-term	inhalation	local	0,05 mg/m³
115-10-6 dimethyl ether	-10-6 dimethyl ether		
Consumer DNEL, long-term	inhalation	systemic	471 mg/m³
Worker DNEL, long-term	inhalation	systemic	1894 mg/m ³

PNEC values

CAS No	Substance		
Environmental	Environmental compartment Value		
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17		
Freshwater		0,001 mg/l	
Marine water		0,0002 mg/l	
Freshwater se	diment	13 mg/kg	
Marine sedime	ent	2,6 mg/kg	
Secondary poi	soning	10 mg/kg	
Micro-organisr	ns in sewage treatment plants (STP)	80 mg/l	
Soil		11,9 mg/kg	
9016-87-9	4,4'-methylenediphenyl diisocyanate, isomers and homologues		
Freshwater 1 mg/l		1 mg/l	
Freshwater (intermittent releases) 10 mg/l		10 mg/l	
Marine water 0,1 mg/l		0,1 mg/l	
Micro-organisms in sewage treatment plants (STP) 1 mg/l		1 mg/l	
Soil		1 mg/kg	
115-10-6	dimethyl ether		
Freshwater		0,155 mg/l	
Freshwater (intermittent releases) 1,549 mg		1,549 mg/l	
Marine water 0,01		0,016 mg/l	
Freshwater sediment 0,681 mg		0,681 mg/kg	
Marine sediment 0,069 mg/kg		0,069 mg/kg	
Micro-organisr	ns in sewage treatment plants (STP)	160 mg/l	
Soil		0,045 mg/kg	

8.2. Exposure controls



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 7 of 16

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. BS/EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. Suitable material: Butyl rubber. (0,5 mm) Breakthrough time >480 min penetration time (maximum wearing period): >160 min The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133).

Use only respiratory protection equipment with CE-symbol including four digit test number.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

. 1. Information on pasic physical and cher	
Physical state:	Aerosol
Colour:	light yellow
Odour:	characteristic
Changes in the physical state	
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	-12 °C
Sublimation point:	not determined
Softening point:	not determined
Flash point:	-83 °C
Flammability	
Gas:	not determined
Explosive properties In case of insufficient ventilation and/c	or through use, explosive/highly flammable mixtures may develop.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Auto-ignition temperature:	not determined
Self-ignition temperature	
Gas:	460 °C



according to UK REACH Regulation

Pistol	enschaum PROFOX® PRO-FOAM 1K 750ml	
Revision date: 06.08.2021	Product code: ZKR13GX	Page 8 of 16
Decomposition temperature:	not determined	
Oxidizing properties none		
pH-Value:	not determined	
Viscosity / dynamic:	not determined	
Viscosity / kinematic:	not determined	
Flow time:	not determined	
Water solubility:	not determined	
Solubility in other solvents not determined		
Vapour pressure: (at 20 °C)	not determined	
Vapour pressure: (at 50 °C)	<3000 hPa	
Density (at 20 °C):	0,979 g/cm³	
Relative vapour density:	not determined	
9.2. Other information		
Other safety characteristics		
Solvent separation test:	not determined	
Solvent content:	not determined	
Solid content:	not determined	
Evaporation rate:	not determined	
Further Information		

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions. Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard. Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Alcohol. amines. Ammonia. strong alkalis. Strong acid. Oxidizing agents, strong. Reducing agents, strong.

10.6. Hazardous decomposition products

Combustible. Vapours may form explosive mixtures with air. Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). Hydrogen chloride (HCI)

Further information

In use, may form flammable/explosive vapour-air mixture.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 9 of 16

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested			
	Dose	Species	Source
LD50, oral	13849,78 mg/kg		in analogy; MSDS extern.
LD50, dermal	>2000 mg/kg		in analogy; MSDS extern.
LC50, inhalation (aerosol) (4 h)	47,71 mg/l		in analogy; MSDS extern.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
85535-85-9	alkanes, C14-17, chloro;	chlorinated p	araffins, C1	4-17		
	oral	LD50 mg/kg	> 4000	Rat	Toxicol. Appl. Pharmacol. 54: 514-525 (1	Groups of at least 3 male and/or female
	dermal	LD50 mg/kg	> 2800	Rat	ECHA Dossier	standard acute method
	inhalation (1 h) vapour	LC50 mg/l	> 48,17	Rat	ECHA Dossier	standard acute method
9016-87-9	4,4'-methylenediphenyl	diisocyanate,	isomers and	homologues		
	oral	LD50 mg/kg	> 2000			
	dermal	LD50 mg/kg	> 2000			
	inhalation (4 h) vapour	LC50	11 mg/l			
	inhalation aerosol	ATE	1,5 mg/l			
25322-69-4	4 Propane-1,2-diol, propoxylated					
	oral	LD50 2000 mg/kg	1000-	Rat	MSDS extern.	
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains isocyanates. May produce an allergic reaction.May cause allergy or asthma symptoms or breathing difficulties if inhaled. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

May cause an allergic skin reaction. (4,4'-methylenediphenyl diisocyanate, isomers and homologues) The product is: sensitizing.

People who suffer from skin sensitazion problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

May cause harm to breast-fed children. (alkanes, C14-17, chloro; chlorinated paraffins, C14-17)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

alkanes, C14-17, chloro; chlorinated paraffins, C14-17:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative. Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Species: Rat; Result: NOAEL = 100 mg/kg; Literature information:



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 10 of 16

ECHA Dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rat; Result: NOAEL = 5000 mg/kg; Literature information: ECHA Dossier

4,4'-methylenediphenyl diisocyanate, isomers and homologues

In vitro mutagenicity/genotoxicity: Method: EU Method B.13/14 (Mutagenicity - Reverse Mutation Test Using Bacteria) Result / evaluation: negative.; In vivo mutagenicity/genotoxicity Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test). Species: Rat. Result / evaluation: negative.; Carcinogenicity: Method: OECD 453. Species: Rat. Exposure duration: 2 years Result / evaluation: NOAEC = 0,2 mg/m³ Air.; Developmental toxicity/teratogenicity: Method: OECD 414. Species: Rat. Result / evaluation: NOAEC = 4 mg/m³ Air. Literature information: ECHA Dossier

STOT-single exposure

May cause respiratory irritation. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (4,4'-methylenediphenyl diisocyanate, isomers and homologues) alkanes, C14-17, chloro; chlorinated paraffins, C14-17: Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Species: Rat Exposure duration: 90d Result: NOAEL = 100 mg/kg Literature information: ECHA Dossier

4,4'-methylenediphenyl diisocyanate, isomers and homologues

Chronic inhalation toxicity: Method: OECD 453. Species: Rat. Exposure duration: 2 years Result / evaluation: NOAEC = 0,2 mg/m³ Air. Literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17						
	Acute fish toxicity	LC50 mg/l	> 10000	96 h	Alburnus alburnus	Publication (1979)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 3,2		Pseudokirchneriella subcapitata	Study report (1997)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,008	48 h	Daphnia magna	Study report (1996)	OECD Guideline 202
	Fish toxicity	NOEC	5,6 mg/l	60 d	Oncorhynchus mykiss	Study report (1983)	OECD Guideline 204
	Crustacea toxicity	NOEC mg/l	0,01	21 d	Daphnia magna	Study report (1997)	other: OECD Guideline 202
115-10-6	dimethyl ether						

according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date	e: 06.08.2021		Prod	uct cod	e: ZKR13GX		Page 11 of 16
	Acute fish toxicity	LC50 mg/l	> 4100	96 h	Poecilia reticulata	ECHA Dossier	NEN 6504 Water - Determination of
	Acute algae toxicity	ErC50 mg/l	154,917	96 h	green algae	ECHA Dossier	Data generated using ECOSAR v1.00
	Acute crustacea toxicity	EC50 mg/l	> 4400	48 h	Daphnia magna	ECHA Dossier	NEN6501: Water -Determination of
25322-69-4	Propane-1,2-diol, propoxy	lated					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Danio rerio	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Desmodesmus subspicatus	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC	(10) mg/l	21 d	Daphnia magna	ECHA Dossier	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Source			
	Evaluation				
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17				
	OECD Guideline 301 D	5%	28	ECHA Dossier	
	Not easily bio-degradable (according to OECD-criteria).				
9016-87-9	7-9 4,4´-methylenediphenyl diisocyanate, isomers and homologues				
	OECD 302	0%	28		
	Not easily bio-degradable (according to OECD-criteria).				
115-10-6	dimethyl ether				
	OECD 301D / EEC 92/69 annex V, C.4-E 5% 28 ECHA Dossier				
	Not easily bio-degradable (according to OECD-criteria).				
25322-69-4	Propane-1,2-diol, propoxylated				
	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D 86,6% 28 ECHA Dossier				
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17	>= 4,7
115-10-6	dimethyl ether	0,07
25322-69-4	Propane-1,2-diol, propoxylated	-0,68 - 0,01

BCF

CAS No	Chemical name	BCF	Species	Source
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17	1087	Oncorhynchus mykiss	Study report (2000)

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The mixture contains the following substances fulfilling the PBT-/vPvB criteria according to REACH Annex XIII: Decamethylcyclopentasiloxane, Dodecamethylcyclohexasiloxane, Octamethylcyclotetrasiloxane



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 12 of 16

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.

According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml			
Revision date: 06.08.2021	Product code: ZKR13GX Page	13 of 16	
14.4. Packing group:	-		
Hazard label:	2.1		
	2		
Classification code:	5F		
Special Provisions:	190 327 344 625		
Limited quantity:			
Excepted quantity:	E0		
Marine transport (IMDG)	101 (050		
14.1. UN number or ID number:	UN 1950		
14.2. UN proper shipping name:	AEROSOLS		
14.3. Transport hazard class(es):	2.1		
14.4. Packing group:	-		
Hazard label:	2.1		
Marine pollutant:	YES		
Special Provisions: Limited quantity:	63, 190, 277, 327, 344, 381, 959 1000 mL		
Excepted quantity:	E0		
EmS:	F-D, S-U		
Air transport (ICAO-TI/IATA-DGR)			
14.1. UN number or ID number:	UN 1950		
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE		
14.3. Transport hazard class(es):	2.1		
14.4. Packing group:	- · ·		
Hazard label:	2.1		
	2		
Special Provisions:	A145 A167 A802		
Limited quantity Passenger:	30 kg G		
Passenger LQ:	Y203		
Excepted quantity:	E0		
IATA-packing instructions - Passenger:	203		
IATA-max. quantity - Passenger:	75 kg		
IATA-packing instructions - Cargo:	203 450 km		
IATA-max. quantity - Cargo:	150 kg		
14.5. Environmental hazards	~		
ENVIRONMENTALLY HAZARDOUS:	Yes		
Danger releasing substance:	alkanes, C14-17, chloro; chlorinated paraffins, C14-17		
14.6. Special procedutions for user			

14.6. Special precautions for user Refer to section 6-8



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 14 of 16

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

_e regulatory mornation	
Restrictions on use (REACH, annex XVII):	
Entry 3, Entry 56	
2010/75/EU (VOC):	21,42 %
2004/42/EC (VOC):	209,71 kg/m³ (209,71 g/L)
Information according to 2012/18/EU (SEVESO III):	E1 Hazardous to the Aquatic Environment
Additional information:	P3a
Additional information	
Aerosol directive (75/324/EEC)	
UK REACH Appendix XVII, No (mixture	e): 3, 28, 40, 56
The mixture is classified as hazardous	according to regulation (EC) No 1272/2008 [CLP].
National regulatory information	

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. 3 - highly hazardous to water

Water hazard class (D):

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: dimethyl ether

SECTION 16: Other information

Changes

Rev. 1.00; 10.12.2015, Initial release Rev. 2,0; 08.06.2018,Changes in chapter: 1-16. Rev. 3,0; 06.08.2021,Changes in chapter: 1-16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures DNEL: Derived No Effect Level d: day(s) EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European LIst of Notified Chemical Substances ECHA: European Chemicals Agency EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 15 of 16

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) h: hour LOAEL: Lowest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect concentration NLP: No-Longer Polymers N/A: not applicable OECD: Organisation for Economic Co-operation and Development PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) REACH: Registration, Evaluation, Authorisation of Chemicals SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe UN: United Nations VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
Resp. Sens. 1; H334	Bridging principle "Aerosols"
Skin Sens. 1; H317	Bridging principle "Aerosols"
Carc. 2; H351	Calculation method
Lact.; H362	Calculation method
STOT SE 3; H335	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.	
H222 Extremely flammable aerosol.	
H229 Pressurised container: May burst if heated.	
H280 Contains gas under pressure; may explode if heated.	
H302 Harmful if swallowed.	
H315 Causes skin irritation.	
H317 May cause an allergic skin reaction.	
H319 Causes serious eye irritation.	
H332 Harmful if inhaled.	
H334 May cause allergy or asthma symptoms or breathing difficultie	es if inhaled.
H335 May cause respiratory irritation.	
H351 Suspected of causing cancer.	
H362 May cause harm to breast-fed children.	
H373 May cause damage to organs through prolonged or repeated	l exposure.
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
EUH066 Repeated exposure may cause skin dryness or cracking.	
EUH204 Contains isocyanates. May produce an allergic reaction.	



according to UK REACH Regulation

Pistolenschaum PROFOX® PRO-FOAM 1K 750ml

Revision date: 06.08.2021

Product code: ZKR13GX

Page 16 of 16

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)